

Enclosures - Standard International Range

<i>Weidmüller</i>	AKZ 1.5	AKZ 4	SAK 2.5	SAK 4	SAK 6 N	SAK 16	SAK 35	WDU 2.5	WDU 4	WDU 6	WDU 10	WDU 16	WDU 35
Terminal rail TS 32			X	X	X	X	X						
Terminal rail TS 35								X	X	X	X	X	X
Bridgeable	X	X	X	X	X	X	X	X	X	X	X	X	X
Connection cross-section (mm) Fine wire	1.5	4	2.5	4	6	16	35	4	6	10	16	16	35
Connection cross-section (mm) Single wire	1.5	4	4	6	10	16	16	4	6	10	16	16	16
Nominal voltage (V)	250	380	750	750	750	750	750	750	750	750	750	750	750
Load (A)	18	34	26	34	44	82	135	26	34	44	61	82	135
Width of terminals (mm)	5	6	6	6.5	8	12	18	5	6	8	10	12	16
Type of enclosure	Number per rail												
PG 120 122 090			12	11	9	6	4	14	12	9	7	6	4
PG 120 220 090			28	26	21	14	9	34	28	21	17	14	10
PG 160 160 090			18	16	13	9	6	21	18	13	10	9	6
PG 160 260 090			34	32	26	17	11	41	34	26	20	17	12
PG 160 360 090			51	47	38	25	17	61	51	38	30	25	18
PG 160 560 090			85	78	63	42	28	102	85	63	51	42	31
PG 250 255 120 *			33	31	25	16	11	40	33	25	20	16	12
PG 250 255 160 *			33	31	25	16	11	40	33	25	20	16	12
PG 250 400 120 *			58	53	43	29	19	70	58	43	35	29	21
PG 250 400 160 *			58	53	43	29	19	70	58	43	35	29	21
PG 250 600 120 *			91	84	68	45	30	109	91	68	54	45	33
PG 360 360 090 **			51	47	38	25	17	61	51	38	30	25	18
PG 405 400 120 **			58	53	43	29	19	70	58	43	35	29	21
* When using terminal blocks of up to 16 mm, maximum of 2 terminal rails possible (double number)													
** When using terminal blocks of up to 10 mm, maximum of 3 terminal rails possible (triple number)													

